

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : arecal Inox Finish stainless steel care 400 ml

Product code : 0895 111 400

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Care product
Professional use product

Recommended restrictions
on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : RECA-uk ltd
Doranda Way, West Bromwich
West Midlands B 71 4LU

Telephone : +44 121 5250525

E-mail address of person
responsible for the SDS : sds@reca.com

1.4 Emergency telephone number

+49 (0)6132 8 44 63
+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)**

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Hazard pictograms :

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27	Asp. Tox. 1; H304	>= 70 - < 90
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280	>= 30 - < 50

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|----------------------------|---|---|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water.
Get medical attention if symptoms occur. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|---|
| Treatment | : | Treat symptomatically and supportively. |
|-----------|---|---|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|--|
| Specific hazards during fire-fighting | : | Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
|---------------------------------------|---|--|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. If spillage enters rivers or watercourses, inform the Environment Agency (emergency telephone number 0800 807060).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Avoid breathing spray.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | Do not spray on an open flame or other ignition source.
If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases |
| Recommended storage temperature | : | < 40 °C |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	TWA	600 ppm 1,450 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	750 ppm 1,810 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
White mineral oil (petroleum)	Workers	Inhalation	Long-term systemic effects	164.56 mg/m ³
	Workers	Skin contact	Long-term systemic effects	217.05 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	34.78 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	93.02 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Equipment should conform to BS EN 166

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Hand protection	
Material	: Nitrile rubber
Glove thickness	: 0.7 mm
Remarks	: Wash hands before breaks and at the end of workday. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
Skin and body protection	: Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to BS EN 137
Filter type	: Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: Aerosol containing a liquefied gas
Propellant	: Butane, Propane, Isobutane
Colour	: clear
Odour	: odourless
Odour Threshold	: No data available
pH	: Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	: 15 %(V)
Lower explosion limit / Lower flammability limit	: 3 %(V)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Vapour pressure	:	3.8 bar (20 °C)
		6.8 bar (50 °C)
Relative vapour density	:	Not applicable
Density	:	0.69 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	> 160 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure :

- Inhalation
- Skin contact
- Ingestion
- Eye contact

Acute toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Butane:

Acute inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapour
---------------------------	---

Skin corrosion/irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species	: Rabbit
Result	: No eye irritation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Butane:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species	:	Rat
---------	---	-----

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Skin contact Result: negative
----------------------	---	--

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
-------------------------------	---	--

Butane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on foetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
-------------------------------	---	--

STOT - single exposure

Not classified based on available information.

Components:

Butane:

Assessment	:	May cause drowsiness or dizziness.
------------	---	------------------------------------

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species	:	Rat
---------	---	-----

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

LOAEL	:	> 160 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Species	:	Rat
LOAEL	:	>= 1 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 412

Butane:

Species	:	Rat
NOAEL	:	9000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

White mineral oil (petroleum):

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOEC: 1,000 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other	:	NOEC: 1,000 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Contaminated packaging : Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product
16 05 04*, gases in pressure containers (including halons) containing hazardous substances

unused product
16 05 04*, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings
15 01 10*, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1950
ADR	: UN 1950
RID	: UN 1950
IMDG	: UN 1950
IATA	: UN 1950

14.2 UN proper shipping name

ADN	: AEROSOLS
ADR	: AEROSOLS
RID	: AEROSOLS
IMDG	: AEROSOLS
IATA	: Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

ADR	:	2	2.1
RID	:	2	2.1
IMDG	:	2.1	
IATA	:	2.1	

14.4 Packing group

ADN

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1

IMDG

Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous	:	no
---------------------------	---	----

ADR

Environmentally hazardous	:	no
---------------------------	---	----

RID

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Marine pollutant	:	no
------------------	---	----

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
-----	--------------------	---------------------	---------------------

18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
----	---	------	-------

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 46 %, 317 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard
Flam. Gas : Flammable gases
Press. Gas : Gases under pressure
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Inox Finish stainless steel care 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 10.06.2024
6.0	05.11.2024	10176515-00007	Date of first issue: 04.11.2021

compile the Safety Data
Sheet

eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1

H222, H229

Classification procedure:

Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN