

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Product code : 0896 215 400

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant
Professional use product

Recommended restrictions
on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : RECA-uk ltd
Doranda Way, West Bromwich
West Midlands B 71 4LU

Telephone : +44 121 5250525

E-mail address of person
responsible for the SDS : sds@reca.com

1.4 Emergency telephone number

+49 (0)6132 8 44 63
+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Aerosols, Category 1

H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dec-1-ene, homopolymer, hydrogenated	68037-01-4 01-2119486452-34	Asp. Tox. 1; H304	>= 10 - < 20
Amines, C12-14-alkyl, isooctyl phosphates	68187-67-7 269-119-5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400	>= 0.1 - < 0.25

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version 7.0	Revision Date: 17.04.2025	SDS Number: 10515423-00009	Date of last issue: 08.11.2024 Date of first issue: 17.12.2021
----------------	------------------------------	-------------------------------	---

		Aquatic Chronic 2; H411	
		M-Factor (Acute aquatic toxicity): 1	
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders	: No special precautions are necessary for first aid responders.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
If spillage enters rivers or watercourses, inform the Environment Agency (emergency telephone number 0800 807060).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absor-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|---|
| Requirements for storage areas and containers | : | Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit
flammable gases
Explosives
Gases

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	TWA	600 ppm 1,450 mg/m3	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	750 ppm 1,810 mg/m3	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Equipment should conform to BS EN 166

Hand protection

Material : Nitrile rubber
Break through time : <= 480 min
Glove thickness : 0.45 mm
Guideline : Equipment should conform to BS EN 374

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Aerosol containing a liquefied gas

Propellant : Isobutane, Propane, Butane

Colour : white

Odour : characteristic

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : -80 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 10.8 %(V)

Lower explosion limit / Lower : 1 %(V)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

|| flammability limit

Vapour pressure : Not applicable

Relative vapour density : Not applicable

|| Density : 0.855 g/cm³ (20 °C)
Method: DIN 51757

|| Solubility(ies)

|| Water solubility : immiscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

|| Viscosity, kinematic : 612 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Amines, C12-14-alkyl, isooctyl phosphates:

Acute oral toxicity	: LD50 (Rat, female): > 200 - 2,000 mg/kg Method: OECD Test Guideline 423
Acute inhalation toxicity	: Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	: LD50 (Rabbit): 2,000 mg/kg

Butane:

Acute inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapour
---------------------------	---

Skin corrosion/irritation

|| Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species	: Rabbit
Result	: No skin irritation

Amines, C12-14-alkyl, isooctyl phosphates:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Corrosive after 4 hours or less of exposure

Serious eye damage/eye irritation

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

Amines, C12-14-alkyl, isooctyl phosphates:

Result	: Irreversible effects on the eye
Remarks	: Based on skin corrosivity.

Respiratory or skin sensitisation

Skin sensitisation

|| Not classified based on available information.

Respiratory sensitisation

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Amines, C12-14-alkyl, isooctyl phosphates:

Test Type	: Maximisation Type
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Germ cell mutagenicity

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Amines, C12-14-alkyl, isooctyl phosphates:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

|| Not classified based on available information.

Reproductive toxicity

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

|| Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

STOT - single exposure

|| Not classified based on available information.

Components:

Butane:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

|| Not classified based on available information.

Repeated dose toxicity

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species : Rat
NOAEL : 4,159.4 mg/kg
Application Route : Ingestion
Exposure time : 91 Days

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Aspiration toxicity

|| Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dec-1-ene, homopolymer, hydrogenated:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Scenedesmus capricornutum (fresh water algae)): > 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOELR (Scenedesmus capricornutum (fresh water algae)): 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to microorganisms	: NOEC : 2 mg/l Exposure time: 28 d Method: OECD Test Guideline 301D
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR: 125 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test substance: Water Accommodated Fraction Method: OECD Test Guideline 211

Amines, C12-14-alkyl, isoctyl phosphates:

Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 17 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 0.8 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

	NOELR (Pseudokirchneriella subcapitata (green algae)): 0.32 mg/l
	Exposure time: 72 h
	Test substance: Water Accommodated Fraction
	Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: 1

12.2 Persistence and degradability

Components:

Dec-1-ene, homopolymer, hydrogenated:

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 2 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301D

Amines, C12-14-alkyl, isooctyl phosphates:

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 35 %
	Exposure time: 28 d
	Method: Directive 67/548/EEC Annex V, C.4.D.

Butane:

Biodegradability	: Result: Readily biodegradable.
	Biodegradation: 100 %
	Exposure time: 385.5 h
	Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Dec-1-ene, homopolymer, hydrogenated:

Partition coefficient: n-octanol/water	: log Pow: > 6.5
--	------------------

Amines, C12-14-alkyl, isooctyl phosphates:

Partition coefficient: n-octanol/water	: log Pow: < 4
	Remarks: Expert judgement

Butane:

Partition coefficient: n-octanol/water	: log Pow: 2.31
--	-----------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)
Waste Code	: The following Waste Codes are only suggestions: used product 16 05 04*, gases in pressure containers (including halons) containing hazardous substances unused product 16 05 04*, gases in pressure containers (including halons) containing hazardous substances uncleaned packagings

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

15 01 10*, packaging containing residues of or contaminated
by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
ADR	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
Tunnel restriction code	: (D)
RID	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Hazard Identification Number	: 23

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
-----	--------------------	---------------------	---------------------

Control of Major Accident Hazards Regulations 2015 (COMAH)

18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
----	---	------	-------

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 59.7 %, 397.25 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220	: Extremely flammable gas.
H280	: Contains gas under pressure; may explode if heated.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

H318 : Causes serious eye damage.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Gas : Flammable gases
Press. Gas : Gases under pressure
Skin Corr. : Skin corrosion
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



arecal Long Lub H1 high-pressure adhesive lubricant 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 08.11.2024
7.0	17.04.2025	10515423-00009	Date of first issue: 17.12.2021

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1

H222, H229

Classification procedure:

Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN